Pos. Art. No. Description Price/Unit Qty Totai [EURI [EURI 1 VEIT 8657 Tunnel Finisher 1+2+3 - 400 V / 50 Hz -170.680,00 170.680,00 consisting of: 124395 1 1.1

VEIT 8657 Tunnel Finisher 1+2+3 base unit -400 V / 50 Hz

incl.

consisting of: 1 air roller unit at entry

1 pre-treatment unit,

 $2\,\mbox{steam}$ units with 128 maintenance free nozzles each

3 Veit "Direct Blow" air units

1 "High-Volume" final unit, for a great "doll" effect

clearance width 260 mm / 10,2 inch Basic price includes:

- program control via Touchscreen Display
- -Integrated program administration via Touchscreen Display
- customizable user interface
- steam spray pressure gauge
- -adjustable steam quality according to the different materials (dry or wet steam)
- -Long Life coating of the inner walls of the steam unit individually adjustable air flow and air temperature in each "Direct-blow" air unit
- -Extra big temperature range up to max. 160°C automatic savety cut-off for the maintenance-free conveyor unit
- progammable piece counter (batch/day)
- password protected user and service area with different authorization
- -doors accessible from both sides (user/service)
- easily maintainable construction
- -removable lint filter, easy to clean by user
- -energy saving heat insulation
- '- pleasant noise level
 - condensate collecting main
 - -twist-proof hanger guidance
 - secure unloading at high speeds
 - -integrated maintenance unit for compressed air
 - evidence of conformity

CE for EMC-compatibility, electric safety, machinery

1.2 124401 1



for optimised steam quality only one steam connection necessary

1.3	124399	controllable steam suction	2	incl.
		For better penetration of humidity> better quality for natural fibres (surcharge for each steam unit)		
1.4	124398	Steam/air separation unit	1	incl.
		for optimised drying effect		
1.5	124400	additiona suctional the entrance	1	incl.
	-	to avoide condensate* recomended for configurations without pre-treatment unit * Unique selling points		
		automatic heightadjustment Ofthe""High-Volume"final		
		unit. Recommended for unsorted flow Ofgarments*		
		Through sensors automatically 4-times ajustable final unit. For more volume of the garments.		
		* Unique selling points		
	1 多地			
				1
	124403		1	incl.
1.7	124408	Roller direct drive	1	incl.
1.8	109836	Separator/loader-hangers from left side long	1	incl.
		Transport of metal and plastic hangers		
	1-12			
1.	9 5862029250	Broad Hangers Guiding at Exit Unit	1	in
		For stabilisation of the garment at the transport conveyor to the feed off		
1.1	10 124407	Rebounding Wall	1	in
		For entry unit, for stabilisation of the garments at the transport conveyor		
1.1	11 5862060930	Electronic Parts Feed on & Feed off	2	in

1.13 105556

Feeding Clip Conveyor 7 + 2 meters

included:
motor with fastening device, 7m Clipconveyor
2m sliding-line, support-scaffold

Subtotal:

181.640,00