


Tier1

BloombergNEF



Lloyd's Syndicate 1910



ISO14001

ISO9001

ISO45001




M10 HIEFF TWIN MONO


SPxxx-108M10

- Standard white (xxx=390~415W)
- Bifacial
- Black frame
- Full black

12 Yr quality guarantee | 25Yr power warranty



*SUNPRO Standard tiered warranty



WARRANTY & GUARANTEE

Linear output power guarantee
12 years: 91.9% power output
25 years: 82.1% power output



WITHSTAND STRONG

Snow load 5400Pa
Wind load 2400Pa



R&D AND PRODUCTION

Advanced production line.
The leading solar cell
cutting process and multi
busbar design with
SUNPRO Technology.



HIGH EFFICIENCY

Efficiency can reach
21.23%. Excellent low light
performance. Higher power
output under the conditions
of haze, overcast, etc.



POWER TOLERANCE


Power positive
tolerance: 0~+3%

Electrical parameters at standard test conditions (STC:AM=1.5, 1000W/m², Cells Temperature 25°C)

Typical type

	390W	395W	400W	405W	410W	415W
Max power(P _{max})	390	395	400	405	410	415
Max power voltage(V _{mp})	30.41	30.62	30.83	31.04	31.25	31.47
Max power current(I _{mp})	12.83	12.90	12.98	13.05	13.12	13.19
Open circuit voltage(V _{oc})	36.53	36.73	36.93	37.13	37.33	37.53
Short circuit current(I _{sc})	13.62	13.69	13.76	13.83	13.90	13.97
Module Efficiency(%)	21.88	20.20	20.46	20.72	20.97	21.23
Max system voltage	DC 1500V(TUV)					
Maximum Series Fuse Rating	25A					


DIMENSIONS AND STRUCTURE



Side

Back

I-V CHARACTERISTICS AT DIFFERENT IRRADIATION



Electrical parameters at NMOT test conditions

(Irradiance 800W/m², Ambient Temperature 20°C, AM 1.5, Wind Speed 1m/s)

Typical type

	390W	395W	400W	405W	410W	415W
Max power(P _{max})	317.4	321.2	325.4	329.2	333.1	337.1
Max power voltage(V _{mp})	30.90	31.10	31.30	31.50	31.70	31.90
Max power current(I _{mp})	10.28	10.34	10.41	10.47	10.52	10.58
Open circuit voltage(V _{oc})	36.70	36.90	37.10	37.30	37.50	37.70
Short circuit current(I _{sc})	10.88	10.93	10.99	11.04	11.10	11.16

Mechanical Data

Dimensions	1724x1134x30mm
Weight	21.5 kg
Glass	3.2mm tempered glass
Output cables	4mm ² , symmetrical lengths 1100mm
Connectors	MC4 compatible IP68
Cell type	Mono-Crystalline PERC, 10BB, 182x91mm
Number of cells	108 cells (Half-Cell)

Temperature Characteristics

Temp.Coeff.of I _{sc} (TK I _{sc})	0.048%/°C	Container	40'HQ
Temp.Coeff.of V _{oc} (TK V _{oc})	-0.27%/°C	Pieces per pallet	72
Temp.Coeff.of P _{max} (TK P _{max})	-0.35%/°C	Pallets per container	13
Operating temperature	-40~+85°C	Pieces per container	936
Normal operating cell temperature	44±2°C		

Packing Configuration

Tests, Certifications and Warranties

Standard tests	IEC 61215, IEC 61730, IEC 61701, IEC 62716, PPP 58042B
System certs	ISO 9001, ISO14001, ISO45001, TUV
Certifications	TUV, AMMONIA AND SALT MIST CORROSION, ANTI-PID, CE, WEEE, INMERTRO, FIRE CERTIFICATE C1
Extreme wind and snow loads testing	Withstand extreme wind(2400 Pascal) and snow loads(5400 Pascal)
Power tolerance	0~+3%
Junction box	IP 68
Warranties	12 years product warranty and 25 years 82.1% of power